

考試編碼:400-051

考試名稱:CCIE Collaboration

版本: Demo

<http://exam24.net/>

QUESTION NO: 1

Company ABC is planning to migrate from MCS-hosted Cisco Unified Communications Manager applications to Cisco UC on UCS B-Series servers. Which statement about installation media support is true for this migration?

- A. The install log can be written to a USB flash drive that is attached to the UCS server.
- B. The answer file that is generated by the Answer File Generator (platformConfig.xml) can be read from a USB flash drive to perform an unattended installation on the UCS server.
- C. The Cisco Music on Hold USB audio sound card can be mapped to a virtual USB port on a VMware virtual machine on the UCS server.
- D. The answer file that is generated by the Answer File Generator (platformConfig.xml) can be read from an FLP image that is mounted in a virtual floppy drive.
- E. The Cisco Music on Hold USB audio sound card can be mapped to a virtual serial port on a VMware virtual machine on the UCS server.

Answer: D

QUESTION NO: 2

Which statement about the Cisco UC on UCS TRC and the third-party server specs-based virtualization support model is true?

- A. Both the UC on UCS TRC and the third-party servers spec-based support models have rulebased approaches.
- B. The UC on UCS TRC support model has a rule-based approach and the third-party servers spec-based support model has a configuration-based approach.
- C. The UC on UCS TRC support model requires a high level of virtualization experience while the third-party server spec-based support model requires a low to medium level virtualization experience.
- D. VMware vCenter is mandatory for the UC on UCS TRC support model but it is optional for the third-party server spec-based support model.
- E. VMware vCenter is optional for the UC on UCS TRC support model but it is mandatory for the third-party server spec-based support model.

Answer: E

QUESTION NO: 3

Which definition is included in a Cisco UC on UCS TRC?

- A. storage arrays such as those from EMC or NetApp, if applicable
- B. configuration of virtual-to-physical network interface mapping
- C. step-by-step procedures for hardware BIOS, firmware, drivers, and RAID setup

- D. server model and local components (CPU, RAM, adapters, local storage) at the part number level
- E. configuration settings and patch recommendations for VMware software

Answer: D

QUESTION NO: 4

Which capability is supported by Cisco Discovery Protocol but not by LLDP-MED?

- A. LAN speed and duplex discovery
- B. network policy discovery
- C. location identification discovery
- D. power discovery
- E. trust extension

Answer: E

QUESTION NO: 5

Which two mechanisms does Cisco EnergyWise use for neighbor discovery? (Choose two.)

- A. multicast
- B. LLDP-MED
- C. UDP broadcast
- D. Cisco Discovery Protocol
- E. TCP

Answer: C,D

QUESTION NO: 6

Which protocol does the Cisco Prime LAN Management Solution application use to communicate with Cisco EnergyWise domain members?

- A. UDP broadcast
- B. Cisco Discovery Protocol
- C. UDP unicast
- D. TCP
- E. multicast

Answer: D

QUESTION NO: 7

Which two SCCP call signaling messages are initiated by Cisco Unified Communications Manager to an IP phone? (Choose two.)

- A. SoftKeyEvent
- B. CloseReceiveChannelAck
- C. CallState
- D. KeypadButton
- E. OpenReceiveChannel
- F. Offhook

Answer: C,E

QUESTION NO: 8

Which statement describes a disadvantage of using the Cisco TFTP service to serve IP phone load files?

- A. The Cisco TFTP services can run on only one Cisco Unified Communications Manager server in a cluster.
- B. Because TFTP operates on top of UDP, there is a high risk of corrupted load file delivery at the completion of the TFTP process due to undetected data loss in the network.
- C. If a response is not received in the timeout period, the TFTP server will not resend the data packet.
- D. Packet loss can significantly increase the TFTP session completion time.
- E. Because TFTP operates with an adaptive timeout period, the time to complete the file transfer is unpredictable.

Answer: D

QUESTION NO: 9

Which two statements about using the Load Server option for IP phone firmware distribution are true? (Choose two.)

- A. This option must be enabled on at least two servers in a Cisco Unified Communications Manager cluster.
- B. This option must be enabled on Cisco Unified Communications Manager service parameters for Cisco TFTP.
- C. Phone firmware must be manually copied to any applicable load servers.
- D. The load server will not function if its IP address is not in the same subnet as the IP phones.

- E. This option is only available for newer IP phone models.
- F. This option does not accommodate falling back to Cisco TFTP on error.

Answer: C,F

QUESTION NO: 10

Which two statements about the Peer Firmware Sharing option for IP phone firmware distribution are true? (Choose two.)

- A. This option uses a parent-child hierarchy in which a firmware image is downloaded by a parent phone to up to three directly associated child phones.
- B. This option must be enabled on Cisco Unified Communications Manager service parameters for Cisco TFTP.
- C. This option mandates that the parent phone and child phones be identical, selected phone models.
- D. This option allows firmware transfers between phones in different subnets, as long as the round-trip delay is less than 5 milliseconds.
- E. This option uses a parent-child hierarchy that must be manually defined by the Cisco Unified Communications Manager administrator.
- F. This option allows falling back to the TFTP server in the Cisco Unified Communications Manager cluster.

Answer: C,F